

REVOLT X ADVANCED PRO 2

GIANT



ESPECIFICACIONES

CUADRO	
TALLAS	XS, S, M, M/L, L, XL
COLORES	Black/Sea Sparkle
CUADRO	Advanced-grade composite, 12x142mm thru-axle, disc, flip chip dropout
HORQUILLA	RockShox Rudy XPLR, 40mm, cartridge damper 12x100mm thru-axle
AMORTIGUADOR	N/A
COMPONENTES	
MANILLAR	Giant Contact SL XR D-Fuse, 31.8mm XS:44cm, S:44cm, M:46cm, M/L:46cm, L:48cm, XL:48cm
PUÑOS	Stratus Lite 3.0
POTENCIA	Giant Contact, 8-degree XS:50mm, S:50mm, M:60mm, M/L:70mm, L:70mm, XL:80mm
TIJA DE SILLÍN	Post Moderne Suspension Dropper, 30.9mm with 30mm of suspension XS:365mm / 75mm drop S:415mm / 100mm drop
SILLÍN	Giant Approach SL
PEDALES	N/A
TRANSMISIÓN	
MANETAS DE CAMBIO	Sram Apex AXS 1X12
DESVIADOR	N/A
CAMBIO TRASERO	Sram X1 AXS Eagle w/ battery protector 1X12
FRENOS	SRAM hydraulic, SRAM PaceLine rotors [F]160mm, [R]160mm
PALANCAS DE FRENOS	SRAM Apex AXS hydraulic, left lever dropper switch
CASETTE	SRAM PG-1230, 12-speed, 11x50
CADENA	SRAM CN-EAGL-NX-A1, 12-speed
JGO. PLATOS Y BIELAS	SRAM Apex 1 Wide DUB, 1X40t XS:170mm, S:170mm, M:172.5mm, M/L:172.5mm, L:175mm, XL:175mm
CAJA DE PEDALIER	SRAM DUB, press fit

RUEDAS	
LLANTAS	Giant CXR X1 WheelSystem, [F] 25.8mm, [R] 25.8mm
BUJES	[F] Giant CXR X alloy, CenterLock, 12mm thru-axle, [R] Giant CXR X alloy, 60t ratchet driver, CenterLock, 12mm thru-axle
RADIOS	Sapim Laser
CUBIERTAS	Maxxis Rambler, 700x45c, tubeless prepared
EXTRAS	tubeless prepared, 53mm max tire size in "long" flip chip position, 45mm max tire size in "short" flip chip position
LÍMITES	
MÁXIMA ANCHURA DE NEUMÁTICO	700x53mm at long RC

Precio: 4.599,00 €

GEOMETRÍA

CUADRO	XS	S	M	ML	L
	SHORT LONG SHORT	LONG SHORT LONG SHORT	LONG SHORT LONG SHORT	LONG SHORT LONG SHORT	LONG SHORT LONG SHORT
Longitud del tubo del sillín (mm)	430	450	470	490	510
Ángulo del tubo del sillín	74,0° 73,9°	73,5° 73,4°	73,5° 73,4°	73,0° 72,9°	73,0°
Longitud del tubo superior (mm) (mm)	543	553	560	575	585
Longitud del tubo de dirección (mm) (mm)	90	100	115	130	145
Ángulo del tubo de dirección	70,5° 70,4°	71,0° 70,9°	71,5° 71,4°	72,0° 71,9°	72,0°
Inclinación de la horquilla (mm)	50	50	50	50	50
Trail (mm) (mm)	80,3 83,7	76,9 80,3	73,5 76,8	70,1 73,4	70,1
Distancia entre ejes (mm) (mm)	1023 1033	1024 1034	1026 1036	1031 1041	1041
Longitud de la vaina (mm) (mm)	425 435	425 435	425 435	425 435	425
Caída del eje de pedalier (mm) (mm)	68 69	68 69	68 69	68 69	68 69
Stack (mm) (mm)	549	560	576	592	607
Reach (mm) (mm)	386	387	389	393	399
Altura del suelo al tubo (mm) (mm)	720 726	736 743	755 761	772 778	790
Ancho del manillar (mm) (mm)	440	440	460	460	480
Longitud de la potencia (mm) (mm)	50	60	70	80	80
Longitud de las bielas (mm) (mm)	170	170	172,5	172,5	175
Tamaño de ruedas	700x 42C	700x 42C	700x 42C	700x 42C	700x 42C

Giant se reserva el derecho a modificar especificaciones, precios o colores sin previo aviso.